



Typical	
Resistance*	22 - 35 Ω
Voltage	180 volts
Current	15 amps
Power	2000 watts
*Resistance Room Temp: R@800°C ~ 1/2R Room Temp	

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MOMENTIVE PERFORMANCE MATERIALS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MOMENTIVE PERFORMANCE MATERIALS IS PROHIBITED. <small>Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.</small>		DIMENSIONS ARE IN: mm [in] TOLERANCES: UNLESS OTHERWISE SPECIFIED ANGULAR: MACH \pm .5° TWO PLACE DECIMAL: \pm .3 [0.01] THREE PLACE DECIMAL: \pm .13 [0.005]		NAME: JMM ENGINEER: TJH APPROVED BY: TJH	DATE: 4/8/08 DATE: 4/16/08		TITLE: HT-44 Standard Heater Final **External Details**	
EXPORT CONTROL STATUS: IS THIS DOCUMENT EXPORT CONTROLLED? No		MATERIAL: PBN/PG TREATMENT: FORMER UCAR/ACC #: HTRJOW, HTR_0690 CUST DWG #:		CNC: ITEM #: HTR0044 CMM#			DRAWING NUMBER: 080395	
TITELBLOCK VERSION: MOMENTIVE TITELBLOCK A INCH V1.0 4/07		RFQ #:		WORK ORDER:	SALES ORDER:	SCALE: 1:1		SHEET 1 OF 1