



Typical	
Resistance*	9 - 15 Ω
Voltage	30 volts
Current	8 amps
Power	150 watts
*Resistance Room Temp: R@800°C ~ 1/2R Room Temp	

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MOMENTIVE PERFORMANCE MATERIALS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MOMENTIVE PERFORMANCE MATERIALS IS PROHIBITED.

Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.

DIMENSIONS ARE IN: INCHES

TOLERANCES: UNLESS OTHERWISE SPECIFIED
 ANGULAR: MACH± .5°
 TWO PLACE DECIMAL: ± 0.01
 THREE PLACE DECIMAL: ± 0.005

NAME

DATE

DRAWN BY: JMM 4/1/08
 ENGINEER: TJH
 APPROVED BY: TJH 4/16/08
 CNC:



TITLE:
 HT-02 Standard Heater Final
 External Details

EXPORT CONTROL STATUS:

IS THIS DOCUMENT EXPORT CONTROLLED? **No**

MATERIAL: PBN/PG
 TREATMENT:
 FORMER UCAR/ACC #: HTR_HT-02, HTR_0138A
 CUST DWG #:

ITEM #: HTR0002
 CMM#
 WORK ORDER: SALES ORDER:

DRAWING NUMBER: 080365 **REV** -

TITLEBLOCK VERSION:

MOMENTIVE TITLEBLOCK A INCH V1.0 4/07

SCALE: 2:1 **SHEET 1 OF 1**