



2x $\phi 4.22 \pm 0.20$ [.166 ± .008] thru
 $\square \phi 9.53 \pm 0.25$ [.375 ± .010]
 contact OD

$\phi 25.4 \pm 0.5$ [1.000 ± .020] O.D.

2.0 [.078]
 2.5 [.098]

Typical	
Resistance*	9 - 15 Ω
Voltage	40 volts
Current	10 amps
Power	300 watts
*Resistance Room Temp: R@800°C ~ 1/2R Room Temp	

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MOMENTIVE PERFORMANCE MATERIALS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MOMENTIVE PERFORMANCE MATERIALS IS PROHIBITED.

Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.

DIMENSIONS ARE IN: mm [in]

TOLERANCES: UNLESS OTHERWISE SPECIFIED
 ANGULAR: MACH $\pm .5^\circ$
 TWO PLACE DECIMAL: $\pm .3$ [0.01]
 THREE PLACE DECIMAL: $\pm .13$ [0.005]

NAME

DATE

DRAWN BY: JMM 3/31/08
 ENGINEER: TJH
 APPROVED BY: TJH 4/16/08
 CNC:



TITLE:
HT-03 Standard Heater
****External Final****

EXPORT CONTROL STATUS:

IS THIS DOCUMENT EXPORT CONTROLLED? **No**

MATERIAL:
 PBN/PG
 TREATMENT:

FORMER UCAR/ACC #:
 HTR_0139A

CUST DWG #:

ITEM #:
 HTR0003

CMM#

DRAWING NUMBER:
080358

REV
 -

TITLEBLOCK VERSION:

MOMENTIVE TITLEBLOCK A INCH V1.0 4/07

RFQ #:

WORK ORDER:

SALES ORDER:

SCALE: 1:1

SHEET 1 OF 1