



Typical	
<b>Resistance*</b>	17 - 30 Ω
<b>Voltage</b>	110 volts
<b>Current</b>	12 amps
<b>Power</b>	1000 watts
*Resistance Room Temp: R@800°C ~ 1/2R Room Temp	

<p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MOMENTIVE PERFORMANCE MATERIALS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MOMENTIVE PERFORMANCE MATERIALS IS PROHIBITED.</p> <p>Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.</p>		<p><b>DIMENSIONS ARE IN: mm[in]</b></p> <p>TOLERANCES: UNLESS OTHERWISE SPECIFIED</p> <p>ANGULAR: MACH± .5°</p> <p>TWO PLACE DECIMAL: ± .3 [0.01]</p> <p>THREE PLACE DECIMAL: ±.13 [0.005]</p>		<p>NAME: JMM</p> <p>DATE: 3/28/08</p>	<p><b>MOMENTIVE™</b></p> <p>TITLE: External Final Details for HT-04 Standard Heater</p>
		<p>EXPORT CONTROL STATUS:</p> <p><b>IS THIS DOCUMENT EXPORT CONTROLLED?</b> <b>No</b></p>		<p>ENGINEER: TJH</p> <p>APPROVED BY: TJH</p> <p>DATE: 4/16/08</p>	
<p>MATERIAL: PBN/PG</p> <p>TREATMENT:</p> <p>FORMER UCAR/ACC #: HTR/VHT-04, HTR_0140A</p> <p>CUST DWG #:</p>		<p>CNC: 803501</p> <p>ITEM #: HTR0004</p> <p>CMM#</p>	<p>WORK ORDER:</p> <p>SALES ORDER:</p>	<p>SCALE: 2:1</p>	<p>SHEET 1 OF 1</p>
<p>TITLEBLOCK VERSION: MOMENTIVE TITLEBLOCK A INCH V1.0 4/07</p>		<p>RFQ #:</p>	<p>WORK ORDER:</p> <p>SALES ORDER:</p>	<p>SCALE: 2:1</p>	<p>SHEET 1 OF 1</p>