



**COATED: 7.4 - 10.1 OHMS**  
**35 VOLTS, 220 WATTS TYPICAL, 8 AMPS MAX**  
**FINAL THICKNESS: 1.4±.25 [.055±.010]**  
**FLATNESS: 1.0/100**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MOMENTIVE PERFORMANCE MATERIALS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MOMENTIVE PERFORMANCE MATERIALS IS PROHIBITED.

Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.

**DIMENSIONS ARE IN: mm [in]**

TOLERANCES: UNLESS OTHERWISE SPECIFIED  
 ANGULAR: MACH ±.5°  
 ONE PLACE DECIMAL: ± .2 [0.008]  
 TWO PLACE DECIMAL: ± .1 [0.004]

	NAME	DATE
DRAWN BY:	JMM	8/29/11
ENGINEER:	NJW	
APPROVED BY:	DAL	12/1/11
CNC:		
ITEM #:	102011	
CMM#		
WORK ORDER:	SALES ORDER:	



**TITLE:**  
**25mm Standard PBN Plate Heater**  
**1mm Base Thickness**  
**\*\*EXTERNAL FINAL\*\***

**DRAWING NUMBER:** 110389  
**REV**: -

**SCALE: 2:1** **SHEET 1 OF 1**

EXPORT CONTROL STATUS:  
**IS THIS DOCUMENT EXPORT CONTROLLED?** **No**

MATERIAL: PBN/PG  
 TREATMENT:  
 FORMER UCAR/ACC #:

CUST DWG #:  
 RFQ #:

TITLEBLOCK VERSION:  
 MOMENTIVE TITLEBLOCK A INCH V1.0 4/07