



Typical	
<b>Resistance*</b>	15 - 25 $\Omega$
<b>Voltage</b>	208 volts
<b>Current</b>	25 amps
<b>Power</b>	4500 watts
*Resistance Room Temp: R@800°C ~ 1/2R Room Temp	

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MOMENTIVE PERFORMANCE MATERIALS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MOMENTIVE PERFORMANCE MATERIALS IS PROHIBITED.

Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.

DIMENSIONS ARE IN: mm [in]		NAME	DATE
TOLERANCES: UNLESS OTHERWISE SPECIFIED		DRAWN BY: JMM	4/8/08
ANGULAR: MACH±.5°		ENGINEER: TJH	
TWO PLACE DECIMAL: ± .3 [0.01]		APPROVED BY: TJH	4/16/08
THREE PLACE DECIMAL: ±.13 [0.005]		CNC:	
		ITEM #: HTR0064	
		CMM#	
		WORK ORDER:	SALES ORDER:



TITLE:  
**HT-64 Standard Heater Final**  
**\*\*External Details\*\***

EXPORT CONTROL STATUS:

**IS THIS DOCUMENT EXPORT CONTROLLED?** **No**

MATERIAL: PBN/PG  
 TREATMENT:  
 FORMER UCAR/ACC #: HT64R1, HTR0658B  
 CUST DWG #:

RFQ #:

DRAWING NUMBER:  
**080407**

REV  
 -

TITLEBLOCK VERSION:  
 MOMENTIVE TITLEBLOCK A INCH V1.0 4/07

SCALE: 1:1

SHEET 1 OF 1