



Typical	
Resistance*	5 - 7 Ω
Voltage	15 volts
Current	8 amps
Power	80 watts
*Resistance Room Temp: R@800°C ~ 1/2R Room Temp	

Ø .500 hot zone

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MOMENTIVE PERFORMANCE MATERIALS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MOMENTIVE PERFORMANCE MATERIALS IS PROHIBITED.
Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.

DIMENSIONS ARE IN: INCHES
TOLERANCES: UNLESS OTHERWISE SPECIFIED
ANGULAR: MACH $\pm .5^\circ$
TWO PLACE DECIMAL: ± 0.01
THREE PLACE DECIMAL: ± 0.005

	NAME	DATE
DRAWN BY:	JMM	3/31/08
ENGINEER:	TJH	
APPROVED BY:	TJH	4/16/08
CNC:		
ITEM #:	HTR0001	
CMM#		
WORK ORDER:		
SALES ORDER:		

MOMENTIVETM

TITLE:
HT-01 Standard Heater Final
****External Details****

DRAWING NUMBER:
080360

REV
-

SCALE: 4:1

SHEET 1 OF 1

EXPORT CONTROL STATUS:
IS THIS DOCUMENT EXPORT CONTROLLED? **No**

TITLEBLOCK VERSION:
MOMENTIVE TITLEBLOCK A INCH V1.0 4/07

MATERIAL:
PBN/PG
TREATMENT:

FORMER UCAR/ACC #:
HT-01 Rev A, HTR_0134B

CUST DWG #:

RFQ #: