



ISOMETRIC VIEW
SCALE 1.5: 2

Typical	
Resistance*	15 - 25 Ω
Voltage	110 volts
Current	15 amps
Power	1300 watts
*Resistance Room Temp: R@800°C ~ 1/2R Room Temp	

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MOMENTIVE PERFORMANCE MATERIALS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MOMENTIVE PERFORMANCE MATERIALS IS PROHIBITED. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.		DIMENSIONS ARE IN: mm[in] TOLERANCES: UNLESS OTHERWISE SPECIFIED ANGULAR: MACH ±.5° TWO PLACE DECIMAL: ± .3 [0.01] THREE PLACE DECIMAL: ± .13 [0.005]		NAME: JMM DATE: 3/28/08	
		EXPORT CONTROL STATUS: IS THIS DOCUMENT EXPORT CONTROLLED? No		DRAWN BY: JMM ENGINEER: TJH APPROVED BY: TJH DATE: 4/16/08	
MATERIAL: PBN/PG TREATMENT: FORMER UCAR/ACC #: HTR/VHT-05, HTR_0141B CUST DWG #:		CNC: ITEM #: HTR0005 CMM#	WORK ORDER: SALES ORDER:	DRAWING NUMBER: 080349	REV: -
TITELBLOCK VERSION: MOMENTIVE TITELBLOCK A INCH V1.0 4/07		RFQ #:	SCALE: 2:1	SHEET 1 OF 1	