



www.momentive.com

260 Hudson River Road Waterford, NY 12188

+1 800 295 2392

Customer Service Centers

Americas +1 800 295 2392 +1 614 986 2495

Europe, Middle East, Africa and India +00 800 4321 1000 +40 213 044229

Email commercial.services@momentive.com

China +800 820 0202

All Other Countries +60 3 9206 1543

Japan

+81 276 20 6182

Korea

+82 2 6201 4688

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or ndation to practice any invention covered by any patent, without authority from the owner of the patent

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES $SHALL\,IN\,NO\,EVENT\,BE\,RESPONSIBLE\,FOR\,ANY\,LOSS\,RESULTING\,FROM\,ANY\,USE\,OF\,ITS\,MATERIALS,\\ PRODUCTS\,OR\,SERVICES\,DESCRIBED$ HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

SilForm, Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.

Copyright 2016 Momentive Performance Materials Inc. All rights reserved.



SilGrip* **Pressure Sensitive Adhesive (PSA) Selector Guide for Tapes**

SilGrip PSA Grade Selector Guide

High Shear/Standard Splicing Tape

PSA590LD and PSA810

Polyester and Polyimide films

Key Features:

- Good adhesion to a variety of surfaces
- High temperature shear resistance
- 180 °C long term, >300 °C short term

Plasma/Flame Spray Tape

PSA518 and PSA6574

Silicone Rubber, Glass Cloth, PTFE, Foil

Key Features:

- Extreme temperature resistance
- Clean removal
- Retention of properties vs Temperature exposure



Electrical Insulation Tape

PSA518, PSA610, PSA595, PSA810 Polyimide, Glass Cloth, PTFE

- Excellent electrical properties, high dielectric strength
- High temperature insulation (180 °C insulation class, 330 °C short duration)
- · Low out-gassing, non-corrosive

Plater's Masking Tape

PSA595, PSA610, PSA510 and PSA810 Polyimide, Polyester, PTFE

- Conformable to irregular surfaces
- No "lifting" at elevated temperatures
- No residue left after delamination with PSA810
- Resistant to solder heat, gold plating, hot air leveling.

Additives

SR545:

MQ resin used to increase peel and cohesion

Catalyst for mica and laminating processes


SS4191 and SS4195:

Mica Tapes & Sheets

PSA590LD:

Optimized condensed SiPSA to consider for flexible mica tapes

Low dust PSA for cleaner process ability and low viscous material for better impregnation



Laminating adhesives

Tack free when cured with SRC18 under heat -Thermo-sealing tapes for mechanical fasteners

Low viscosity adhesive providing low tack when cured with SRC18 at room temperature.

Heat Seal - PTFE Glass Fabrics

Ultimate grade for high temp. performance

High temperature shear strength methyl PSA

General propose for "first quality" PTFE glass fabrics