

Esca™ FG10 Antifoam

Product Description

Esca FG10 antifoam is a highly effective silicone-based antifoam emulsion, which has been developed for use in the many applications where quick knockdown of foam is required.

Key Features and Typical Benefits

- Outstanding reliability and versatility
- Highly effective, enabling attainment of foam control with minimum addition of non-nutrient additives
- Available in easy-to-use emulsion form

Typical Physical Properties

Appearance	Off white viscous emulsion
Specific Gravity at 25 °C	1.0
Percentage Silicone	10

Typical properties are average data and are not to be used as or to develop specifications.

Storage and Shelf Life

The product should be stored below 32 °C and ideally should not be allowed to freeze. Shelf life of the unopened container is 12 months from date of manufacture. If you wish to use the product after this time please contact us for approval.

Potential Applications

Esca FG10 antifoam is recommended for a wide variety of aqueous processes (for non-aqueous applications we normally recommend Antifoam C100F). Esca FG10 antifoam is effective as a processing aid in many food processing applications thanks to its knockdown efficiency and speed, that make it a versatile foam control agent.

Esca FG10 antifoam offers many advantages in manufacturing of a wide range of chemicals and subsequent compounds and formulations. Esca FG10 antifoam effectiveness, inert nature and low level of use allow minimal interference in the process and subsequent applications. The product is ideally suited for use in water and effluent treatment. It is easily diluted with water, for an easier addition. Its non-toxic properties mean little interference with biological treatment processes.

For regulatory information contact us at the address below.

General Considerations for Use

Esca FG10 antifoam disperses easily in both warm (<45 °C) and cold aqueous systems, requiring only mild agitation to disperse it completely in the foaming system. For maximum efficiency and economy, we recommend the antifoam be diluted with water before use. The quantity of antifoam required can only be found by experiment. In general, between 100 and 500 ppm of the product is all that is required (500 ppm = 0.5 litres of product per 1000 litres of foaming media).

Trace Analysis of Foodstuffs for Silicone

We are able to advise customers on analytical methods for determining trace quantities of silicone in foodstuffs.

Toxicity

The components of Esca FG10 antifoam have a very low order of toxicity, although prolonged contact with the skin or contact with the eyes may cause some irritation. See our antifoam health and safety sheet for more information.

Technical Service

Our technical and sales staff have considerable experience with the use of silicone products in a wide variety of industries and the benefit of this experience is freely available to all our customers.

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment, if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

Customer Service Centers

For additional information, please contact our Customer Service Team

AMERICAS	+1 800 295 2392 Toll Free* +704 805 6946 Direct Number
LATIN AMERICA	BRAZIL +55 11 4534 9650 Direct Number MEXICO +52 55 2169 7670 Direct Number *All American countries
EMEI - EUROPE, MIDDLE EAST, AFRICA & INDIA	EUROPE +390510924300 Direct Number INDIA, MIDDLE EAST & AFRICA +91 44 71212207 Direct Number* *All Middle Eastern countries, Africa, India, Pakistan, Bangladesh, Sri Lanka
ASIA PACIFIC	CHINA 800 820 0202 Toll Free +86 21 3860 4892 Direct Number JAPAN +81 3 5544 311 Direct Number KOREA +82 2 6201 4600 Direct Number SOUTH EAST ASIA, AUSTRALIA & NEW ZEALAND +60 3 9206 1543 Direct Number* *All East Asia countries (Malaysia, Singapore, Thailand, Indonesia, Vietnam, Philippines, Cambodia, Myanmar / other countries located in Pacific region)
Visit us at www.momentive.com	

DISCLAIMER - THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS, INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER") ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS, OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, OR SERVICES DESCRIBE HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right.

The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials, Inc. or its affiliated companies.

Momentive and the Momentive logo are registered trademarks of Momentive Performance Materials, Inc.

Copyright 2023 Momentive Performance Materials, Inc. All rights reserved.



260 Hudson River Road
Waterford, NY 12188 USA
momentive.com