

## Magnasoft™ 2059 Textile Softener

### Product Description

Magnasoft 2059 textile softener is a self-cross-linkable silicone emulsion of an amino-functional silicone polymer in water. This product cures to an elastomeric film without the need for a catalyst.

Magnasoft 2059 textile softener is manufactured without alkyl phenol-based chemicals (APEO).

### Key Features and Typical Benefits

- Forms a film as soon as the water evaporates
- Outstanding slickness along with soft hand-feel
- Exceptional stretch recovery and bouncy hand-feel to all types of fabrics
- Minimizes wrinkles on fabrics
- Moderate water repellent
- Good shear stability
- Typically economical to use
- Produced without alkyl phenol-based chemicals (APEO)

### Typical Physical Properties

Appearance	Milky white liquid
Solid Content (%)	35
Viscosity, 25 °C, #3/6	< 50 cPs
Specific Gravity, 25 °C (77 °F)	1.0
Ionic Character	Cationic
Suitable Dilutant	Water

Typical properties are average data and are not to be used as or to develop specifications.

### Potential Applications

- Virtually any type of fabric requiring excellent smoothness and bouncy softness
- Mercerized cotton knits
- Wool/wool-blended knits and worsted wool woven
- Fiber and thread lubricants
- Improved softness in wrinkle-free finish
- Hand-feel modifier for PU leather and natural leather

### General Considerations for Use

Magnasoft 2059 textile softener is provided in a ready-to-use, high-solids content form that can be applied as received. Because of its high solids content, however, it is advisable to dilute Magnasoft 2059 textile softener prior to adding to the textile finish bath.

The optimum dosage depends on the required softness, type of fabric and fabric finish conditions, but the following are common initial rates.

#### 1. Pad-dry-cure continuous process

Dosage	:	10 ~ 30 g/L
pH	:	6.0 ~ 8.0
Temperature	:	Ambient
Pick-up	:	65 ~ 100 %
Drying	:	100 ~ 130 °C x 1 - 3 minutes

## 2. Exhaustion process

Dosage	:	1.0 ~ 3.0 % on the weight of fabric
Liquor Ratio	:	1/10 ~ 1/20
pH	:	6.0 ~ 8.0
Temperature	:	20 ~ 40 °C
Time	:	15 ~ 30 minutes
Drying	:	100 ~ 120 °C

### Cure Properties

Upon evaporation of water, the product will cure to an elastomeric film.

## Precautions

### 1. Dilute with cold or warm water

Magnasoft 2059 textile softener is generally stable in hard water. However, should the water supply be of 200 ppm hardness or higher, softened water or boiler condensate is recommended as a diluent.

### 2. Compatibility

Magnasoft 2059 textile softener may not be compatible with certain materials, such as anionics, lower alcohols, salts, etc., which may break the silicone emulsion. Any mixture of reactive emulsions with other materials should be thoroughly checked before it is put into factory production.

## Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

## Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at [www.momentive.com](http://www.momentive.com) or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

## Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

## Customer Service Centers

For additional information, please contact our Customer Service Team

<b>AMERICAS</b>	+1 800 295 2392 Toll Free* +704 805 6946 Direct Number
<b>LATIN AMERICA</b>	<b>BRAZIL</b> +55 11 4534 9650 Direct Number <b>MEXICO</b> +52 55 2169 7670 Direct Number *All American countries
<b>EMEA – EUROPE, MIDDLE EAST, AFRICA &amp; INDIA</b>	<b>EUROPE</b> +390510924300 Direct Number <b>INDIA, MIDDLE EAST &amp; AFRICA</b> +91 44 71212207 Direct Number* *All Middle Eastern countries, Africa, India, Pakistan, Bangladesh, Sri Lanka
<b>ASIA PACIFIC</b>	<b>CHINA</b> 800 820 0202 Toll Free +86 21 3860 4892 Direct Number <b>JAPAN</b> +81 3 5544 311 Direct Number <b>KOREA</b> +82 2 6201 4600 Direct Number <b>SOUTH EAST ASIA, AUSTRALIA &amp; NEW ZEALAND</b> +60 3 9206 1543 Direct Number* *All East Asia countries (Malaysia, Singapore, Thailand, Indonesia, Vietnam, Philippines, Cambodia, Myanmar / other countries located in Pacific region)
<b>Visit us at <a href="http://www.momentive.com">www.momentive.com</a></b>	

**DISCLAIMER** - THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBE HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies.

Momentive and the Momentive logo are registered trademarks of Momentive Performance Materials Inc.

Copyright 2022 Momentive Performance Materials Inc. All rights reserved.



260 Hudson River Road  
Waterford, NY 12188 USA  
[momentive.com](http://momentive.com)