SILCOOL[™] TIA268GF LIQUID-DISPENSED SILICONE THERMAL PAD / GAP FILLER

Product Description

SILCOOL TIA268GF silicone is a 2-component, soft, thermally conductive material that can dissipate heat from electronic devices. Its non-slumping pasty consistency can provide physical stability for optimized processing. It can be used as liquid dispensed alternative to pre-fabricated thermal pads, for a broad array of thermal designs in electronic applications.

Key Features and Typical Benefits

- High thermal conductivity
- Fast, low temperature cure
- Convenient 1:1 mix ratio by weight
- Retains softness after cure to contribute to stress relief during thermal cycling
- Good slump resistance (stays in place)
- Repairable

Typical Physical Properties

| UNCURED PROPERTIES | | TIA268GF (A) | TIA268GF (B) |
|---|-----------------------|------------------|--------------|
| Appearance (Part A & B) | | pink | pale pink |
| Viscosity *1 | Pa∙s | 240 | 255 |
| Mix ratio by weight | | 1:1 | |
| Viscosity *1 after mixing | Pa∙s | 250 | |
| Thixo Index | | 1.5 | |
| Work Life @ 23°C | Hours | 1 | |
| Cure conditions | Hours | | |
| @ 70°C | | 1 | |
| @ 23°C | | 24 | |
| CURED PROPERTIES (1 hour @ 70°C) | | I | |
| Appearance | | pi | nk |
| Density (23°C) | g/cm ³ | 2.9 | |
| Thermal conductivity *2 | W/m·K | 6.8 | |
| Thermal resistance *3 | mm ² • K/W | 10 (at min. BLT) | |
| Minimum Bond Line Thickness | μm | 35-55 | |
| Hardness (Type E) | | 35 | |
| Hardness (Shore 00) | | 60 | |
| Tensile strength | MPa | 0.05 | |
| Elongation | % | 60 | |
| Dielectric strength | kV/mm | 15 | |
| Low volatile (D ₄ -D ₁₀) | ppm | 100 | |

*1: Measured at 20°C with 20mm plate/plate rheometer / *2: Hot disk method / *3: ASTM Typical properties are average data and are not to be used as or to develop specifications.

Potential Applications

Thermal interface for electronic components in automotive, consumer, telecommunication, lighting and industrial applications

General Considerations for Use

- Materials such as water, sulfur, nitrogen compounds, organic metallic salts, phosphorus compounds, etc. contained in the surface of the substrate can inhibit curing. A sample patch should always be conducted before proceeding to determine compatibility.
- Wear eye protection when handling uncured rubber as it can irritate eyes. In case of eye contact, immediately flush eyes well with water and contact a physician.
- Maintain adequate ventilation in the work place at all times.

Option for Glass Beads

Glass Bead versions for BLT control can be made available upon request (typically sizes 180µ and 250µ)

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

- Store in a cool, dry place out of direct sunlight
- Keep out of the reach of children

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at <u>www.momentive.com</u> or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

Contact Information

Email: commentive.com

| Telephone | | | |
|-----------------|------------------|---|------------------|
| Americas | Latin America | EMEAI- Europe, Middle East, Africa & India | ASIA PACIFIC |
| +1 800 295 2392 | Brazil | Europe | China |
| Toll free* | +55 11 4534 9650 | +390510924300 | 800 820 0202 |
| +704 805 6946 | Direct Number | Direct number | Toll free |
| Direct Number | | | +86 21 3860 4892 |
| | | | Direct number |
| | | | |
| *All American | Mexico | India, Middle East & Africa | Japan |
| countries | +52 55 2169 7670 | + 91 44 71212207 | +81 3 5544 3111 |
| | Direct Number | Direct number* | Direct number |
| | | | |
| | | *All Middle Eastern | Korea |
| | | countries, Africa, India, | +82 2 6201 4600 |

Pakistan, Bangladesh, Sri Lanka. Direct number

South East Asia, Australia & New Zealand +60 3 9206 1543 Direct number*

*South East Asia countries (Malaysia, Singapore, Thailand, Indonesia, Vietnam, Philippines, Cambodia, Myanmar / other countries located in Pacific region).

For literature and technical assistance, visit our website at: www.momentive.com

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND **INVOICES**, AND AVAILABLE UPON **REQUEST. ALTHOUGH** ANY INFORMATION. RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

The use of the "TM" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.



260 Hudson River Road Waterford, NY 12188 USA momentive.com

Copyright 2023 Momentive Performance Materials Inc. All rights reserved.