

SNAPSIL™ TUV3805D-LB UV DUAL CURE SILICONE

Product Description

SNAPSIL™ TUV3805D-LB is a one-component UV curable silicone sealing material. It can be selectively dispensed on display modules and can also provide flowability to penetrate tight spaces. TUV3805D-LB silicone features a UV cure formulation that enables faster cure and physical stability with exposure to UV light, followed by a secondary room temperature or thermal cure mechanism that gradually improves adhesion to the substrate. The secondary cure feature also can help achieve more complete cure in shadow areas where UV light penetration is limited. TUV3805D-LB silicone has soft post-cure properties that can contribute to stress-relief of delicate electronics components.

Key Features and Typical Benefits

- Convenient, one-part solution
- Fast UV primary cure, which can contribute to reduction in cycle times
- Secondary room temperature cure to build adhesion and cure shadow sections
- Provides good electrical properties

Typical Physical Properties

. ypicar i mysicar i roperties		
	Unit	TUV3805D-LB
Uncured Properties		
Appearance		Light Blue
Viscosity (20 rpm)*1	Pa.s	3.5
Thixotropic index*1		1.0
Primary Cure(UV)	LED 365 nm	5,000 mJ/cm2
Secondary Cure	50% RH	25°C for 3days
Density	g/cm3	1.01
Hardness	Shore A	30
Tensile strength	MPa	0.7
Elongation	%	120
Adhesion strength*2	MPa	1.0
Tack free time by only moisture, without UV	min	30
Low Volatile Siloxane	Ppm (D4~D10)	<300
Shelf life*3	month	9

^{*1:} viscosity – 20 rpm, Rheometer, Thixotropic Index – 10 rpm /20 rpm, Rheometer

Typical properties are average data and are not to be used as or to develop specifications.

^{*2:} Glass, FR-4 Lap shear

^{*3:} storage condition sealed at 5°C

General Considerations for Use

- A sample patch should always be tested prior to proceeding in order to determine compatibility.
- All parts should be as clean and dry as possible prior to application.
- Eye protection and protective gloves should be always worn when working with this product.
- Always maintain adequate ventilation in the workplace.
- Keep out of the reach of children.

Storage

- Store in a cool dry place out of direct sunlight
- Shelf life at below 5°C is 9 months

Available Package

- 300ml Cartridge
- 50ml EFD Syringe

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

Contact Information

Fmail

commercial.services@momentive.com

Telephone

Americas Latin America EN

EMEAI- Europe, Middle East, Africa & India **ASIA PACIFIC**

+1 800 295 2392 Toll free* +704 805 6946 **Direct Number**

countries

Brazil +55 11 4534 9650 **Direct Number**

Europe +390510924300 Direct number

China 800 820 0202 Toll free

+86 21 3860 4892 Direct number

*All American Mexico

+52 55 2169 7670 **Direct Number**

India, Middle East & Africa +914471212207 Direct number*

Japan +81 3 5544 3111 Direct number

*All Middle Eastern countries, Africa, India, Pakistan, Bangladesh, Sri Lanka.

Korea +82 2 6201 4600 Direct number

South East Asia, Australia & New Zealand

+60 3 9206 1543 Direct number*

*South East Asia countries (Malaysia, Singapore, Thailand, Indonesia, Vietnam, Philippines, Cambodia, Myanmar / other countries located in Pacific region).

literature and technical assistance. visit our website www.momentive.com

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

The use of the "TM" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.



260 Hudson River Road Waterford, NY 12188 USA momentive.com

Copyright 2022 Momentive Performance Materials Inc. All rights reserved.