Technical Data Sheet



IS 5128 E

IS 5128 E

Description

IS 5128 E adhesive/sealant is a one component neutral RTV which quickly cure to form elastic, flexible silicone rubbers. This product is specially developed to be non-corrosive to metals including copper and copper alloys, coupled with fast cure. IS 5128 E has a thixotropic paste consistency, excellent dielectric properties and excellent primerless adhesion to plastics like polycarbonate, which make these materials ideal for electronic applications as well as for sealing bonding high performance plastics.

Key Features and Benefits

- non-corrosive to metals
- fast cure
- non-acid cure, low smell, no irritating vapours
- compatible with polycarbonate
- excellent dielectric properties
- temperature -50° to +150° C

Typical Physical Properties

Typical Uncured Properties

| - | |
|-------|---------|
| | |
| | E400 E |
| | 51/8 F |
| | 0.120 2 |
| | |

| Colour | | Translucent |
|------------------------------------|---------|-------------|
| Density | g/cm³ | 1.03 |
| Tack Free Time | minutes | 10 |
| Consistency | | Paste |
| Application rate, 6mm orifice/2bar | g/min | 250 |

Typical Cured Properties

| Property | Test Method | Unit | Typical value |
|-----------------------------|-------------|---------|---------------|
| Hardness | DIN 53505 | Shore A | 20 |
| E Mod @ 100% | DIN 53504 | MPa | 0.35 |
| Tensile Strength | DIN 53504 | MPa | 1.7 |
| Elongation | DIN 53504 | % | 550 |
| Dielectric Strength | | kV/mm | 25 |
| Dielectric Constant (50 Hz) | | | 2.8 |
| Dissipation Factor (50 Hz) | | | 0.005 |
| Volume Resistivity | | ohm-cm | 1x1015 |

Patent Status

Standard copy to come

Product Safety, Handling and Storage

Standard copy to come

Limitations

Standard copy to come

Contact Information

Email

commercial.services@momentive.com

Telephone

| Americas | Latin America | EMEAI- Europe, Middle East, Africa & India | ASIA PACIFIC |
|--------------------------------|---|---|---|
| +1 800 295 2392 Toll free* | Brazil +55 11 4534 9650 | Europe +390510924300 | China 800 820 0202 |
| +704 805 6946 Direct Number | Direct Number | Direct number | Toll free +86 21 3860 4892 |
| Direct Number | | | Direct number |
| *All American countries | Mexico +52 55 2169 7670 Direct Number | India, Middle East & Africa + 91 44 71212207 Direct number* | Japan +81 3 5544 3111 Direct number |
| | | *All Middle Eastern countries, Africa, India, | Korea +82 2 6201 4600 |

For literature and technical assistance, visit our website at: www.momentive.com

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. **EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE.** SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS. PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and

perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

The use of the "TM" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.