

SAG* 7133

Description

SAG 7133 antifoam emulsion and its more concentrated version, SAG 220 antifoam emulsion, are excellent candidates for controlling foam in amine and glycol dehydration units. Both have been extensively tested in a variety of gas plants and have demonstrated excellent stability in the presence of salts, resulting in reduced deposits on the plant's equipment. SAG 7133 and SAG 220 help preserve foam control under the severe conditions of a dehydrating unit. These conditions can remove water from other antifoam emulsions, rendering them immediately inactive. SAG 47 antifoam compound is the product of choice if the antifoam is to be stored in extreme climate conditions, especially for very cold weather. It can easily be diluted to reduce its viscosity and actives.

Key Features and Benefits

- Quick foam knockdown - particularly useful when foam suddenly builds up in the absorber and rapid control is needed.
- Excellent antifoam stability and durability - over a period of time the concentration of salts in an amine or glycol dehydration unit can reach high levels. SAG 7133 antifoam emulsion and its more concentrated version, SAG 220 antifoam emulsion, are very stable in their presence. Additionally, lower amounts of antifoam are needed to retain line control, potentially resulting in lower costs and reduced propensity for fouling and clogging. Further, since these products are easily dispersed in water and are compatible with glycols, they do not allow the presence of these glycols to easily remove water from their state of emulsion, thus remaining effective for a longer period.
- Excellent stability at high temperatures - because of their excellent dispersibility. SAG 7133 antifoam emulsion and SAG 220 antifoam emulsion do not show a propensity to deposit on heat exchangers as many other antifoams tend to. Instead, they remain finely dispersed in the amine or glycol solution and are eventually filtered out.

- Easy dilution and use - simple addition of water and minimum agitation is sufficient to dilute SAG 7133 antifoam emulsion and SAG 220 antifoam emulsion to required concentrations. Pumping of the diluted emulsions is easy, due to their low viscosity.
- Reduced clogging or scaling in the heat exchangers - potentially resulting in less service maintenance.
- Low concentrations can provide effective foam control - SAG 7133 antifoam emulsion and SAG 220 antifoam emulsion are often two to three times more effective than other antifoams used in gas treating units.

Typical Physical Properties

Emulsion: Silicone Antifoam Emulsion SAG 7133	
Chemical Nature	Emulsion of a silicone antifoam compound
Appearance	White, homogeneous, slightly viscous liquid
Viscosity at 25°C, cSt	600
Active Ingredients, %	10
Specific Gravity at 25°/25°C	1
pH	7
Emulsion Type	Non-ionic
Suitable Diluents	Water only
Emulsion: Silicone Antifoam Emulsion SAG 220	
Chemical Nature	Emulsion of a silicone antifoam compound
Appearance	White, homogeneous, slightly viscous liquid
Viscosity at 25°C, cSt	600
Active Ingredients, %	20
Specific Gravity at 25/25°C	1
pH	7
Emulsion Type	Non-ionic
Suitable Diluents	Water only
Compound: Silicone Antifoam Compound SAG 47	
Chemical Nature	Polydimethyl siloxane compound
Appearance	Translucent white
Viscosity at 25°C, (after stirring), cP	2500

Active Ingredients, % by weight	100
Specific Gravity at 25°/25°C	0.988
Emulsifiers	None
Suitable Diluents	Process liquid, hydrocarbons

Potential Applications

SAG 7133 antifoam emulsion, its more concentrated version, SAG 220 antifoam emulsion, and SAG 47 antifoam compound are targeted for gas recovery plants, where natural gas must be washed, or scrubbed, before distribution, and for liquefied natural gas (LNG) plants that must achieve high gas purity before liquefaction.

In many amine units, foam can be problematic. Proper line control without antifoam is, generally, extremely difficult.

General-purpose antifoams have a wide range of applicability, but not all of them are suitable for use in the treatment of gas. Some foam control agents can aggravate the problem. Foam control in gas scrubbers is only one of the process parameters to be monitored. It is equally important to prevent or slow the fouling of the unit, because dismantling of the gas-scrubbing units is manually intensive. Incorrectly specified antifoams can easily lead to increased fouling and clogging, particularly in the heat exchangers. Momentive Performance Materials SAG antifoams are designed to provide foam control with a minimum of such problems.

Patent Status

Standard copy to come

Product Safety, Handling and Storage

Standard copy to come

Limitations

Standard copy to come

お問合せ窓口

製品の価格、取り扱い状況およびご注文については、[Momentive.com/Contact us/ CustomerService/](https://www.momentive.com/Contact-us/CustomerService/)からカスタマーサービスへご連絡ください。

パンフレットおよび技術情報については、弊社ウェブサイトwww.momentive.comをご覧ください。

免責条項:

モメンティブ・パフォーマンス・マテリアルズならびにその子会社および関係会社(以下、総称して「サプライヤー」といいます)の素材、製品およびサービスは、サプライヤーの標準販売条件に基づき販売されています。この標準販売条件は、該当する販売代理店契約または販売契約に含まれており、注文確認書や請求書の裏面に印刷され、また要求に応じて提供可能です。本書に記載の情報、推奨、または提言は、誠意をもって提供されていますが、サプライヤーは明示的にも黙示的にも、(i)本書に記載の結果が最終使用条件下でも得られること、および(ii)製品、素材、サービス、推奨または提言に取り入れられている設計の有効性もしくは安全性について、いかなる保証もいたしません。サプライヤーの標準販売条件に定めのあるものを除き、サプライヤーおよびその代理人は、本書に記載の素材、製品またはサービスの使用によって生じたいかなる損害に対しても責任を負わないものとします。サプライヤーの素材、サービス、推奨、または提言が、ユーザー自身の特定の使用目的に適しているか否かの判断については、各ユーザー自身が全面的に責任を負います。各ユーザーは、すべてのテストや分析を特定および実施して、サプライヤーの製品、素材、またはサービスが組み込まれている最終製品が安全であり、最終使用条件における使用に適していることを確認する必要があります。サプライヤーの署名入りの書面による合意がない限り、本書もしくはその他の文書または口頭による推奨または提言は、サプライヤーの標準販売条件の規定または本免責条項の変更、修正、優先、または権利放棄とはみなされないものとします。本書に含まれる素材、製品、サービスまたは設計の使用可能性または使用提案に関するいかなる記載も、当該使用または設計を対象とするサプライヤーの特許その他の知的財産権に基づくライセンスを付与することを意図してはならず、あるいはライセンスの付与と解釈してはならず、また、何らかの特許その他の知的財産権を侵害する素材、製品、サービスまたは設計の使用の提案を意図してはならず、また使用提案として解釈してはなりません。

Momentive および Momentiveのロゴは、Momentive Performance Materials Inc.の商標です。