#### **Technical Data Sheet**



# CLS5000 CLS5000

## **Description**

CLS5000 is a transparent, self-bonding, two-component silicone rubber for use in low temperature curing liquid injection molding in the production of high performance elastomeric parts. CLS5000 is clear, but easily pigmentable. CLS5000 offers a convenient 1:1 mix ratio, high tensile strength, and high tear strength. Cure time is rapid depending upon part size, configurations and molding temperature.

## **Key Features and Benefits**

- High clarity for excellent visibility
- Excellent tear strength
- Convenient 1:1 mix ratio for use with automatic equipment
- Rapid cure time depending upon part size, configuration and molding temperature
- Compatible with a wide variety of thermoplastics for injection molding

## **Typical Physical Properties**

| Uncured Properties  |       |  |  |
|---|-------|--|--|
| Cure Rate (Monsanto Rheometer MDR 2000 @177°C or 350°F; w/ Mylar Sheets |       |  |  |
| Torque, maximum, in/lb  | 29.09 |  |  |
| Peak Rate, in/lb/min  | 163.9 |  |  |
| T-2, seconds  | 5.4   |  |  |

| T-90, seconds                           | 25    |  |  |
|---|-------|--|--|
| Cured Properties                        |       |  |  |
| ASTM slabs cured 15 min @ 177°C (350°F) |       |  |  |
| Color                                   | Clear |  |  |
| Specific Gravity                        | 1.12  |  |  |
| Hardness, Shore A durometer             | 67    |  |  |
| Tensile Strength, psi                   | 1,591 |  |  |
| Elongation, %                           | 458   |  |  |
| 100% Modulus, psi                       | 575   |  |  |
| Tear Die B, ppi                         | 261   |  |  |

# Regulatory Compliance

- A representative sample of an analogous product to CLS 5000 met the requirements of USP Class VI and ISO 10993 under Good Laboratory Practices (GLP).
- Compositionally compliant with 21 CFR 177.2600 Rubber articles intended for repeated use<sup>(1)</sup>
- (1) It is the responsibility of the user to determine that the final product complies with the extractive limitations and other requirements of 21 CFR 177.2600, under their specific manufacturing procedures

#### **Patent Status**

Standard copy to come

# **Product Safety, Handling and Storage**

Standard copy to come

#### Limitations

Standard copy to come

### **Contact Information**

Email commercial.services@momentive.com

| Telephone       |                  |                              |                  |
|-----------------|------------------|------------------------------|------------------|
| Americas        | Latin America    | <b>EMEAI- Europe, Middle</b> | ASIA PACIFIC     |
|                 |                  | East, Africa & India         |                  |
| +1 800 295 2392 | Brazil           | Europe                       | China            |
| Toll free*      | +55 11 4534 9650 | +390510924300                | 800 820 0202     |
| +704 805 6946   | Direct Number    | Direct number                | Toll free        |
| Direct Number   |                  |                              | +86 21 3860 4892 |
|                 |                  |                              | Direct number    |
| *All American   | Mexico           | India, Middle East &         | Japan            |
| countries       | +52 55 2169 7670 | Africa                       | +81 3 5544 3111  |
|                 | Direct Number    | + 91 44 71212207             | Direct number    |
|                 |                  | Direct number*               |                  |
|                 |                  | *All Middle Eastern          | Korea            |
|                 |                  | countries, Africa, India,    | +82 2 6201 4600  |

For literature and technical assistance, visit our website at: www.momentive.com

## **DISCLAIMER:**

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE

FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

\*Silopren™ é uma marca registrada da Momentive Performance Materials Inc.

The use of the "TM" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.